

CRONO

Incasso architettonico orientabile con anello di battuta.




Adjustable architectural recessed fitting with stop ring.

Proiettori professionali per incasso in controsoffitto in cartongesso. Realizzati in pressofusione di alluminio e con anello di battuta in colore bianco. Orientabilità rispetto la verticale 30° e rotazione di 360°. Ottica secondaria antiabbagliamento per un elevato confort visivo (UGR<15), disponibile in finitura nero cromo e bianca. Fornito completo di driver ON-OFF. Dimmerabile DALI su richiesta. Grado di protezione IP44, classe di isolamento III, marchio F.



Professional projectors for recessed plasterboard false ceilings. Made of die-cast aluminum and with white stop ring. Adjustability with respect to the vertical 30° and rotation of 360°. Anti-glare secondary optic for high visual comfort (UGR<15), available in black chrome and white finish. Degree of protection: IP44, electrical insulation class III, F mark. Supplied complete with ON-OFF driver. DALI dimmable on request.






Item: RAA6207R--
Power: 7W
Beam angle: 45°
Output flux: 496 lm
Temp. Color: 3.000K
CRI: >90
Face ring: white
Driver: on-off (F), Dali (D)
IP44 (driver IP20)



Item: RAA8312R--
Power: 12W
Beam angle: 50°
Output flux: 860 lm
Temp. Color: 3.000K
CRI: >90
Face ring: white
Driver: on-off (F), Dali (D)
IP44 (driver IP20)



Item: RAA10620R--
Power: 20W
Beam angle: 40°
Output flux: 1643 lm
Temp. Color: 3.000K
CRI: >90
Face ring: white
Driver: on-off (F), Dali (D)
IP44 (driver IP20)



CODIFICA PRODOTTI / PRODUCT CODING

Family name	Dimension hole	Power LED (W)	With ring/trimless	Type of driver On-off/Dali	Optical finish Black chrome/white
RAA	62 \ 83 \ 106	7 \ 12 \ 20	R \ T	F \ D	1 \ 2