

IDRO

Faretto incasso fisso IP65
alto confort.



*High comfort fixed IP65
recessed spotlight.*

Proiettori professionali fissi per incasso in controsoffitto in cartongesso con grado di protezione IP65. Realizzati in pressofusione di alluminio e con anello di battuta in colore bianco. Ottica secondaria antiabbagliamento per un elevato confort visivo (UGR<19), disponibile in finitura nero cromo e bianca. Grado di protezione IP65, classe di isolamento III, marchio F. Fornito completo di driver ON-OFF. Dimmerabile DALI su richiesta.


Professional fixed projectors for recessed installation in plasterboard false ceilings with IP65 protection degree. Made of die-cast aluminum and with white stop ring. Anti-glare secondary optic for high visual comfort (UGR <19), available in black chrome and white finish. Degree of protection: IP65, electrical insulation class III, F mark. Supplied complete with ON-OFF driver. DALI dimmable on request.



Item: RFE8710R--
Power: 10W
Beam angle: 60°
Output flux: 790 lm
Temp. Color: 3.000K
CRI: >90
Face ring: white
Driver: on-off (F), Dali (D)
IP65



Cutout: Ø75 mm



Nero/Black



1


Bianco/White




2



Item: RFE13525R--
Power: 25W
Beam angle: 60°
Output flux: 1980 lm
Temp. Color: 3.000K
CRI: >90
Face ring: white
Driver: on-off (F), Dali (D)
IP65



Cutout: Ø125 mm



Nero/Black



1

Bianco/White



2

CODIFICA PRODOTTI / PRODUCT CODING

Family name	Dimension hole	Power LED (W)	With ring	Type of driver On-off/Dali	Optical finish Black/white
RFE	75 \ 125	10 \ 25	R	F \ D	1 \ 2